

FIXED INDUCTORS FOR POWER INDUCTORS / THT TYPE

FEATURES


- ◆ Ultra low buzz noise, due to composite construction.
- ◆ The High current (I_{sat} up to 28A) through hole type.
- ◆ Magnetically shielded, suitable for high density mounting.
- ◆ High energy storage and low DCR.
- ◆ Material: Iron Core / Ni-Zn Core (N)





APPLICATIONS

Excellent for power line DC-DC conversion applications used in power switching, personal computers and other handheld electronic equipment..

ORDERING CODE



DIMENSIONS (UNIT: mm)



A	11.8 (MAX)	m/m
B	11.8 (MAX)	m/m
C	3.5 ± 0.5	m/m
D	10.5 (MAX)	m/m



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>

FIXED INDUCOTRS FOR POWER INDUCTORS / THT TYPE

ELECTRICAL CHARACTERISTICS FOR THT1110N

Part No.	Inductance (uH)	RDC (mΩ)	IDC (A) MAX
THT1110N-R30M	0.30	0.80	50
THT1110N-R40M	0.40	0.90	46
THT1110N-R47M	0.47	1.00	42
THT1110N-R56M	0.56	1.10	40
THT1110N-R68M	0.68	1.20	36
THT1110N-R80M	0.80	1.30	34
THT1110N-1R0M	1.00	1.50	32
THT1110N-1R5M	1.50	1.80	18
THT1110N-2R2M	2.20	2.20	14
THT1110N-3R3M	3.30	3.50	12
THT1110N-4R7M	4.70	5.00	10

* Test Frequency : 1KHZ/0.25V



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>