

SHIELDED SMD POWER INDUCTORS / NR(M) TYPE

FEATURES


- ◆ Low profile construction and miniature size
- ◆ Magnetic shielded construction
- ◆ High current saturation
- ◆ For new generation portable product D/D converter unit.
- ◆ Metal alloy core






APPLICATIONS

- ◆ For small DC/DC converter(cellular phone, HDD, DVC, DSC, LCD display etc).


ORDERING CODE



DIMENSIONS (UNIT: mm)



Recommended Land Pattern



Unit : mm

A	2.0 ± 0.3	m/m
B	1.6 ± 0.3	m/m
C	1.0 (MAX)	m/m
D	0.6 (REF)	m/m
E	1.7 ± 0.3	m/m
G	0.60 (REF)	m/m
H	1.70 (REF)	m/m
I	0.85 (REF)	m/m

CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>



SHIELDED SMD POWER INDUCTORS / NR(M) TYPE

ELECTRICAL CHARACTERISTICS FOR NR2010M

Part No.	Inductance (μ H)	Test Frequency (MHz)	RDC (m Ω) MAX	IDC (A) MAX
NR2010M-R24 □	0.24	1MHz / 1V	34	5.60
NR2010M-R33 □	0.33	1MHz / 1V	40	4.80
NR2010M-R47 □	0.47	1MHz / 1V	48	3.60
NR2010M-R68 □	0.68	1MHz / 1V	56	3.00
NR2010M-1R0 □	1.00	1MHz / 1V	75	2.40
NR2010M-1R5 □	1.50	1MHz / 1V	120	1.80
NR2010M-2R2 □	2.20	1MHz / 1V	160	1.55
NR2010M-3R3 □	3.30	1MHz / 1V	230	1.25
NR2010M-4R7 □	4.70	1MHz / 1V	340	1.00
NR2010M-6R8 □	6.80	1MHz / 1V	540	0.84
NR2010M-100 □	10.0	1MHz / 1V	685	0.75