

SHIELDED SMD POWER INDUCTORS / SPI TYPE

FEATURES


- ◆ With magnetic shield against radiation
- ◆ Compact, low profile with low RDC and large current
- ◆ Flat bottom surface allows for reliable mounting onto the board





APPLICATIONS

- ◆ Industrial power modules.
- ◆ DC/DC converters, etc.
- ◆ Various categories of consumer electronics.

ORDERING CODE



DIMENSIONS (UNIT: mm)



A	6.0 ± 0.2	m/m
C	2.8 ± 0.2	m/m
D	4.0 (REF)	m/m
E	2.0 (REF)	m/m



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>

SHIELDED SMD POWER INDUCTORS / SPI TYPE

ELECTRICAL CHARACTERISTICS FOR SPI0603

Part No.	Inductance (μ H)	RDC (Ω)	IDC (A)
SPI0603-2R7 □	2.7	0.040	2.50
SPI0603-3R3 □	3.3	0.050	2.35
SPI0603-4R7 □	4.7	0.055	1.90
SPI0603-6R8 □	6.8	0.090	1.78
SPI0603-100 □	10	0.150	1.40
SPI0603-150 □	15	0.170	1.35
SPI0603-180 □	18	0.200	1.10
SPI0603-220 □	22	0.250	0.95
SPI0603-330 □	33	0.300	0.80
SPI0603-470 □	47	0.450	0.70
SPI0603-680 □	68	0.500	0.60
SPI0603-101 □	100	1.100	0.40
SPI0603-151 □	150	1.500	0.33

* 100 μ H 以上 Test Frequency : 1KHZ/1V

* 100 μ H 以下 Test Frequency : 1KHZ/0.25V



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>