

SHIELDED SMD POWER INDUCTORS / SPI TYPE

FEATURES


- ◆ With magnetic shield against radiation
- ◆ Compact, low profile with low RDC and large current
- ◆ Flat bottom surface allows for reliable mounting onto the board






APPLICATIONS

- ◆ Portable telephones.
- ◆ Personal computers.
- ◆ DC/DC converters, etc.
- ◆ Other various electronic appliances.

ORDERING CODE



DIMENSIONS (UNIT: mm)



A	7.0 ± 0.2	m/m
C	3.2 ± 0.2	m/m
D	4.9 (REF)	m/m
E	2.0 (REF)	m/m



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>

SHIELDED SMD POWER INDUCTORS / SPI TYPE

ELECTRICAL CHARACTERISTICS FOR SPI0703

Part No.	Inductance (μ H)	RDC (Ω)	IDC (A)
SPI0703-1R0 □	1.0	0.025	7.00
SPI0703-2R2 □	2.2	0.030	4.50
SPI0703-3R3 □	3.3	0.035	3.20
SPI0703-4R7 □	4.7	0.040	2.80
SPI0703-6R8 □	6.8	0.060	2.30
SPI0703-100 □	10	0.080	1.90
SPI0703-150 □	15	0.095	1.45
SPI0703-220 □	22	0.170	1.30
SPI0703-330 □	33	0.160	1.10
SPI0703-470 □	47	0.268	0.96
SPI0703-680 □	68	0.350	0.80
SPI0703-101 □	100	0.450	0.60
SPI0703-151 □	150	1.000	0.50
SPI0703-221 □	220	1.500	0.35
SPI0703-102 □	1000	4.200	0.20

* 100 μ H 以上 Test Frequency : 1KHZ/1V

* 100 μ H 以下 Test Frequency : 1KHZ/0.25V



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>