

## SHIELDED SMD POWER INDUCTORS / SPI TYPE

### FEATURES


- ◆ With magnetic shield against radiation
- ◆ Compact, low profile with low RDC and large current
- ◆ Flat bottom surface allows for reliable mounting onto the board




### APPLICATIONS

- ◆ Portable telephones.
- ◆ Personal computers.
- ◆ DC/DC converters, etc.
- ◆ Other various electronic appliances.

### ORDERING CODE



### DIMENSIONS (UNIT: mm)



A	$12.5 \pm 0.30$	m/m
C	$7.5 \pm 0.35$	m/m
D	8.6 (REF)	m/m
E	2.0 (REF)	m/m



**CORE MASTER ENTERPRISE CO., LTD.**

<http://www.coremaster.com.tw>

## SHIELDED SMD POWER INDUCTORS / SPI TYPE

### ELECTRICAL CHARACTERISTICS FOR SPI1208

Part No.	Inductance ( $\mu$ H)	RDC ( $\Omega$ )	IDC (A)
SPI1208-6R8 □	6.8	0.030	9.50
SPI1208-100 □	10	0.035	8.00
SPI1208-150 □	15	0.050	7.00
SPI1208-220 □	22	0.060	5.80
SPI1208-330 □	33	0.080	4.50
SPI1208-470 □	47	0.125	4.10
SPI1208-680 □	68	0.157	3.30
SPI1208-101 □	100	0.250	2.70
SPI1208-221 □	220	0.430	2.00
SPI1208-471 □	470	0.770	1.35

\* 100 $\mu$ H 以上 Test Frequency : 1KHZ/1V

\* 100 $\mu$ H 以下 Test Frequency : 1KHZ/0.25V



**CORE MASTER ENTERPRISE CO., LTD.**

<http://www.coremaster.com.tw>