

SURFACE MOUNT HIGH CURRENT POWER INDUCTORS /SMPI-E TYPE

FEATURES


- ◆ Magnetic shielding structure: excellent resistance to electromagnetic interference (EMI).
- ◆ Die-casting by low loss alloy powder: low impedance.
- ◆ High efficiency, wide application frequency and application scope.




APPLICATIONS

- ◆ Servers.
- ◆ Graphics cards.
- ◆ Various categories of consumer electronics.

ORDERING CODE



DIMENSIONS UNIT: mm



A	4.0± 0.3	m/m
B	4.0 ± 0.3	m/m
C	4.0 (REF)	m/m
D	2.1 (MAX)	m/m
E	1.2 (REF)	m/m



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>

SURFACE MOUNT HIGH CURRENT POWER INDUCTORS /SMPI-E TYPE

ELECTRICAL CHARACTERISTICS FOR SMPI 04020E

Part No.	Inductance (uH) @0A	Test Frequency	Heat Rating Current Irms(A)	Saturation Current Isat (A) drop30%	RDC (mΩ) MAX
SMPI04020E-R22M	0.22	100KHz/1V	24.0	25.0	2.6
SMPI04020E-R47M	0.47	100KHz/1V	13.2	16.0	4.4
SMPI04020E-R68M	0.68	100KHz/1V	10.0	12.5	6.4
SMPI04020E-1R0M	1.00	100KHz/1V	14.0	11.0	8.9
SMPI04020E-1R5M	1.50	100KHz/1V	6.0	10.0	20.0
SMPI04020E-2R2M	2.20	100KHz/1V	5.0	8.0	34.0
SMPI04020E-3R3M	3.30	100KHz/1V	4.5	6.0	43.0
SMPI04020E-4R7M	4.70	100KHz/1V	4.0	5.5	63.0
SMPI04020E-5R6M	5.60	100KHz/1V	4.0	5.3	67.0
SMPI04020E-100M	10.00	100KHz/1V	3.4	4.9	125.0
SMPI04020E-220M	22.00	100KHz/1V	1.7	2.8	280.0

Notes:

- 1) You require another part number please contact with us.
- 2) Inductance Tolerance $\pm 20\%$; Frequency Test : 100KHz/1.0v
- 3) All test data is referenced to 25°C ambient.
- 4) Irms : DC current (A) that will cause an approximate ΔT of 40°C
- 5) Isat : DC current (A) that will cause L_o to drop approximately 30%
- 6) We can design according to customer's request.



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>