

SURFACE MOUNT HIGH CURRENT POWER INDUCTORS /SMPI-E TYPE

FEATURES


- ◆ Magnetic shielding structure: excellent resistance to electromagnetic interference (EMI).
- ◆ Die-casting by low loss alloy powder: low impedance.
- ◆ High efficiency, wide application frequency and application scope.




APPLICATIONS

- ◆ Servers.
- ◆ Graphics cards.
- ◆ Various categories of consumer electronics.

ORDERING CODE



DIMENSIONS UNIT: mm



A	6.4± 0.3	m/m
B	6.6 ± 0.3	m/m
C	5.3 (REF)	m/m
D	6.1 (MAX)	m/m
E	1.4 (REF)	m/m



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>

SURFACE MOUNT HIGH CURRENT POWER INDUCTORS /SMPI-E TYPE

ELECTRICAL CHARACTERISTICS FOR SMPI 06060E

Part No.	Inductance (uH) @(0A)	Test Frequency	Heat Rating Current Irms(A)	Saturation Current Isat (A) drop30%	RDC (mΩ) MAX
SMPI06060E-3R3M	3.3	100KHz/1V	13	15.0	13.0
SMPI06060E-4R7M	4.7	100KHz/1V	11	10.5	14.4
SMPI06060E-6R8M	6.8	100KHz/1V	9	9.5	20.8
SMPI06060E-8R2M	8.2	100KHz/1V	8	8.4	26.0
SMPI06060E-100M	10.0	100KHz/1V	7	7.6	29.8

Notes:

- 1) You require another part number please contact with us.
- 2) Inductance Tolerance $\pm 20\%$; Frequency Test : 100KHz/1.0v
- 3) All test data is referenced to 25°C ambient.
- 4) Irms : DC current (A) that will cause an approximate ΔT of 40°C
- 5) Isat : DC current (A) that will cause Lo to drop approximately 30%
- 6) We can design according to customer's request.



CORE MASTER ENTERPRISE CO., LTD.

<http://www.coremaster.com.tw>